

## **LD223**

## Low Density Polyethylene Film Extrusion Grade

Grade Additive packages Applications:

LD223 Slip (750ppm), Antiblock (1000 ppm) Cast Film, Light Duty Shrink Film, FFS Packaging
LD223A Slip (None), Antiblock (None) Foam Application, Freezer Film, Lamination

## PRODUCT DESCRIPTION

LD223 is designed for film extrusion applications with very good optical and strength properties for general purpose clarity packaging. LD223 exhibits good impact strength. LD223 offers excellent extrusion processing and film optical properties.

		Metric Units		English	
Properties*	Test Method	Typical Value	Unit	Typical Value	Unit
Melt Flow Index	ASTM D1238	2.00	g/10 min.	2.00	g/10 min
Density (23°C)	ASTM D1505	0.923	g/cm³	0.923	g/cm³
Film Properties¹					
Dart Drop Impact Strength F50	ASTM D1709	80	g	80	g
Tensile Strengh at Break					
MD	ASTM D882	24	MPa	3600	psi
TD	ASTM D882	22	MPa	3200	psi
Tensile Strengh at Yield					
MD	ASTM D882	11	MPa	1600	psi
TD	ASTM D882	11	MPa	1600	psi
Tensile Elongation at Break					
MD	ASTM D882	330	%	330	%
TD	ASTM D882	550	%	550	%
1 % Secant Modulus					
MD	ASTM D882	207	MPa	30000	psi
TD	ASTM D882	227	MPa	33000	psi
Elmendorf Tear Strength					
MD	ASTM 1922	150	g	150	psi
TD	ASTM D1922	120	g	120	psi
Haze	ASTM D1003	6.1	%	5	%
Gloss	ASTM D2457	63	%	63	%

<sup>\*</sup> Typical Value of Properties which can vary with in specification limits and are not to be construed as specifications.

The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, ICD America LLC disclaims responsibility for reliance and results of use of this information. ICD AMERICA LLC DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ICD America LLC expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.