

## Polypropylene, Homopolymer

Injection Molding

## Icelene 3409

### PRODUCT DESCRIPTION

Icelene 3409 is typically used in spunbond and continuous filament applications that require superior spinnability and finer fibers. The product has gas-fading resistant, good processing stability, narrow molecular weight distribution. It is primarily designed for flexible packaging and textile applications.

Icelene 3409 is also used in extrusion coating application

### PROCESSING METHOD

Cast film; Extrusion Coating; Injection Molding; Spunbond

### APPLICATIONS

- Food Packaging Film
- Hygiene Non woven
- Intermediate Bulk Containers
- Protective clothes; Wipes/Tissues

Properties	Test Method	English		SI	
		Typical Value	Unit	Typical Value	Unit
Melt Flow Index (230°C/2.16 kg)	ASTM D1238	34	g/10 min.	34	g/10 min
Density	ASTM D792	0.9	g/cc	0.9	g/cc

The technical information, suggested uses and applications presented are made without change and are believed to be reliable; however ICD America LLC disclaims responsibility for reliance and results of use of this information. ICD AMERICA LLC DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ICD America expressly disclaims any statement or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.