

HP200N

Polypropylene, Homopolymer Injection grade

PRODUCT DESCRIPTION

Icelene HP200N is a certified prime homopolymer with nucleation to provide fast cycle time and improve contact clarity in thin wall multi-cavity molds. ICELENE Polypropylene HP200N complies with all applicable FDA regulations for food contact applications.

Product features good colorability, flow and stiffness. It can be used both in compounding and injection molding, thin wall containers

APPLICATIONS

- Containers
- Other Industrial application
- caps and closures
- Leisure and Toys

Properties*	Test Method	Typical Value	Unit
Melt Flow Index (230°C/2.16 kg)	ASTM D1238	20	g/10 min.
Density,	ASTM D1505	0.905	g/cc
Tensile	ASTM D638	5500(37.9)	psi(MPa)
Flexural Modulus	ASTM D790	220,000(1520)	psi(MPa)
Tensile Modulus	ASTM D638	260,000(1790)	psi(MPa)
Elongation	ASTM D638	13	%
Izod Impact 73 °F	ASTM D256A	0.5(26.7)	ft-lbs/in(J/m)
Hardness	ASTM D785A	107	Rockwell R
Melting Point	DSC	330(165)	°F(°C)

* These are typical properties : not to be construed as specification.

The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, ICD America LLC disclaims responsibility for reliance and results of use of this information. ICD AMERICA LLC DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ICD America LLC expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.